



Unmatched Quality Tiles

16" x 16"
Outdoor
Floor Tiles



E-VFT-1616-DP2-004
Light Grey
Matt Random



E-VFT-1616
DP2-005 Dark Grey
Matt Random





Unmatched Quality Tiles

E-VFT-1616-003
Bluish Grey Matt
Random



E-VFT-1616-011
Medium Grey Matt
Random



E-VFT-1616-001
Brownish Grey Matt
Random



E-VFT-1616-002
Pinkish Grey Matt
Random



E-VFT-1616-004
Spotted Grey Matt
Random



E-VFT-1616-005
Bluish Grey Matt
Random



E-VFT-1616-010
Yellowish Grey Matt
Random



E-VFT-1616-DP2-001
Pinkish Grey Matt
Random



E-VFT-1616-DP2-002
Light Grey Matt
Random



E-VFT-1616-DP2-003
Grey Matt
Random
















- VFT has a wide range of designs especially for outdoor use.
- Stile Vitrified Floor Tiles are slip resistant with high grip.
- Low maintenance and easy to clean.

Stile Outdoor Floor Tiles



Unmatched Quality Tiles

TECHNICAL CHARACTERISTICS
Vitrified Tiles, ISO 13006 Group Blla

S. No		Technical Characteristics	Test Standard	Permissible Tolerance as per ISO norms	Stile Value
DIMENSION AND SURFACE QUALITY					VITRIFIED TILE
1		Dimension Deviation in percentage from work size length and width	ISO 10545-2	± 0.6 %	± 0.4 %
2		Thickness (Deviation in Percentage)	ISO 10545-2	± 5 %	± 3 %
3		Straightness of sides (Maximum Deviation Percentage)	ISO 10545-2	± 0.5 %	± 0.3 %
4		Rectangularity (Maximum Deviation Percentage)	ISO 10545-2	± 0.6 %	± 0.4 %
5		Surface Flatness	ISO 10545-2	± 0.5 %	± 0.3 %
PHYSICAL PROPERTIES					
6		Water Absorption %	ISO 10545-3	3 % < E ≤ 6 %	3 % < E ≤ 5 %
7		Modulus of rupture	ISO 10545-4	> 22 N/mm ²	> 25 N/mm ²
8		Breaking Strength	ISO 10545-4	> 1000 N	>1200 N
9		Resistance to surface abrasion	ISO-10545-7	Min Class III	Class IV
11		Thermal Shocks Resistance	ISO 10545-9	Resistant	Resistant
12		Crazing Resistance	ISO 10545-11	No Crazing	No Crazing
CHEMICAL PROPERTIES					
13		Resistance to house hold chemical	ISO 10545-13	Min. Class-B	Class-A
14		Resistance to staining	ISO 10545-14	Min Class-3	Class-5

- Slight variation in size and shade is inherent in the manufacture of ceramics tiles.
- It is recommended that several cartons be opened and their contents checked and assembled to an ideal color combination.
- Please inspect all tiles prior to installation, company will not entertain complaints, once tile are laid/fixes.

Outlets Address:

Karachi

Stile Emporium & Design Studio – DHA Bukhari

Plot 22-C Lane 4, Bukhari Commercial, Phase-VI DHA, Karachi.
Phone: +92-21-37249564

Stile Emporium & Design Studio – 26th Street

Plot No: C-8-C, 26th Street, Phase-V, DHA, Karachi.
Phone: +92-21-37228922

Stile Emporium & Design Studio – Star Gate

Metro Cash & Carry, Near Star Gate, Main Sharah-e-Faisal, Karachi.
Phone: +92-21-34601372-74

Stile Emporium – Factory Outlet

15th Milestone, National Highway, Landhi, Karachi.
Phone: +92-21-35015024-25,
+92-21-38183610-11

Hyderabad

Stile Emporium & Design Studio – Hyderabad

Shop No. 11 & 12 Ground Floor Auto Bhan Towers, Auto Bhan Road Opposite Breeze Fish Point Latifabad No. 3, Hyderabad.
Phone: +92-22-6112857

Lahore

Stile Emporium & Design Studio – DHA Lahore

90, CCA, Phase-IV, DHA, Lahore.
Phone: +92-42-37185710-12

Stile Emporium at Sanitar Lifestyle

E-105-1-C, Main Boulevard, Defence, Lahore.

Faisalabad

Stile Emporium & Design Studio – Faisalabad

Talha Heights P-243, 2-A Main Susan Road (Near Khyber Bank), Faisalabad.
Phone: +92-41-8739988

Rawalpindi

Stile Emporium & Design Studio – Rawalpindi

Al Shareef Plaza, Ground Floor, Shamsabad, Main Muree Road, Rawalpindi.
Phone: +92-51-4935521-23



Unmatched Quality Tiles